

.

High grinding capacity. Outstanding end products.



Dolomit allows high-capacity and consistent grinding of wheat, corn/maize, rye, barley, spelt, and other grain varieties. Its rugged design ensures reliable round-theclock operation. Optimal geometry and air flow control satisfy the most rigorous sanitation standards and ensure dust-free operation.

Options:

- Direct aspiration system
- Integrated through-spouts
- Manual roll removal device
- One motor drive for MDDQ eight-roller mill

Customer value:

- Uniform feed rate
- High-capacity grinding
- Reliable operation
- Optimal sanitation
- Easy-to-use operator interface

Rugged, proven technology. Reliable operation.



Uniform feed rate

The wide inlet and the variable roll speed ensure uniform product feed across the entire length of the grinding rolls.



High-capacity grinding The compact roll pack with self-contained forces ensures a high setting accuracy and grinding stability. The low-maintenance toothed gear transmission guarantees smooth running.



Easy-to-use operator interface The easy-to-use operator interface with display panel allows permanent monitoring of all operating parameters.



Reliable operation

The proven roll pack and the sturdy machine frame ensure reliable operation with a consistent grinding quality.

Optimal sanitation. High product safety.



Optimal sanitation

Thanks to the optimal geometry of the components in contact with the product, this roller mill fulfills sanitation standards. The partitioned paneling offers easy access to the grinding rolls. The feed chamber can be cleaned without leaving over any residues, thanks to the patented swing-out feed module.




Optimized machine operation


The user-friendly operation of the roller mill is based on an ergonomic clamping device for adjusting the grinding rolls and optimally positioned handles.



Easy roll changes The optional roll removal device allows fast, easy, and safe roll changes.


Universal application. Suits any production plant.






Technical data of MDDP four-roller mill

Roll diameter (mm)	Roll length (mm)	Dimensions (mm)		Approx. weights (kg)		Volume (m ³)	
		Α	В	R	Net	Packing	Packing
250	800	1610	1493	535	2650	2990	7.6
250	1000	1810	1493	535	2930	3290	7.8
250	1250	2060	1493	535	3430	3800	8.3
300	1000	1810	1693	565	3600	3900	8.5
300	1250	2060	1693	565	3960	4260	9.5





Technical data of MDDQ eight-roller mill, roll diameter 250 mm

Roll length (mm)	Dimensions (mm)	Approx. v	Volume (m ³)	
	Α	Net	Packing	Packing
1000	1940	5070	5440	8.2
1250	2190	6060	6480	9.1

Flyer MDDP-MDDQ en 0916 ZACC

Bühler AG CH-9240 Uzwil, Switzerland T +41 71 955 11 11 F +41 71 955 66 11 www.buhlergroup.com

